



Belshe Industries, Inc  
 PO Box 626  
 Tecumseh, OK 74873  
 Phone (405) 273-1690  
 www.belshetrailers.com

<b>BF8T (T16)</b>	<b>HEAVY DUTY LOW PROFILE</b>
-------------------	-------------------------------

FEATURE TYPE	STANDARD MODEL FEATURES & MEASUREMENTS
<b>GVWR</b>	16,000 lbs.
<b>TRAILER WEIGHT (MIN)</b>	4,460 lbs.
<b>TRAILER DIMENSIONS</b>	
<b>Deck Length</b>	16 ft.
<b>Width Between Fenders</b>	80.75 in.
<b>Overall Width</b>	100.75 in.
<b>Dovetail Length</b>	21 in.
<b>Dovetail Width</b>	Full Width
<b>Deck Height</b>	22 in.
<b>Fender Height</b>	13 in.
<b>Tongue Length</b>	68.5 in.
<b>Ramp Length</b>	5 ft.
<b>Overall Length</b>	23 ft.
<b>RUNNING GEAR</b>	
<b>Axles</b>	8,000 lbs. Belshe Axles (x2)
<b>Brakes</b>	Electric
<b>Suspension</b>	6-Leaf 2 in. Slipper Spring
<b>Wheels</b>	17.5 in. 10-Bolt Superior Single
<b>Tires</b>	215 75R 17.5
<b>FRAME MATERIAL</b>	
<b>Outer Rails</b>	3.5 in. x 6 in. x 0.375 Angle A-36
<b>Cross Members</b>	4 in. x 5.4 lb. Channel A-36
<b>Tongue</b>	10 in. x 15.3 lb. Channel A-36
<b>Fender</b>	10 Gauge Formed
<b>LOADING CONFIGURATION</b>	
<b>Ramps</b>	60 in. x 18 in. Ladder Bar Spring Assisted Adjustable Width
<b>OTHER FEATURES</b>	
<b>Hitch</b>	2.5 in. Pintle Ring
<b>Cargo Control</b>	D-Rings
<b>Flooring</b>	2 in. x 8 in. #1 Grade Treated Pine
<b>Jack</b>	12,000 lbs. Drop Leg
<b>Lighting</b>	LED, Sealed Wiring Harness
<b>Paint</b>	Primed, Acrylic Enamel – Black or Yellow Standard

**OPTIONAL UPGRADES**

- |          |                 |                    |                            |
|----------|-----------------|--------------------|----------------------------|
| ✓ Length | ✓ Gooseneck     | ✓ Custom Color     | ✓ Special Machine Packages |
| ✓ Width  | ✓ Cargo Control | ✓ Polyurea Coating |                            |
| ✓ Ramps  |                 |                    |                            |