

Belshe Industries, Inc PO Box 626 Tecumseh, OK 74873 Phone (405) 273-1690 www.belshetrailers.com

## BF10T

## **HEAVY DUTY LOW PROFILE**

FEATURE TYPE	STANDARD MODEL FEATURES & MEASUREMENTS
GVWR	20,000 lbs.
TRAILER WEIGHT (MIN)	5,000 lbs.
TRAILER DIMENSIONS	
Deck Length	16 ft.
Width Between Fenders	81.5 in.
Overall Width	102 in.
Dovetail Length	33 in.
Dovetail Width	Full Width
Deck Height	25 in.
Fender Height	10 in.
Tongue Length	80 in.
Ramp Length	5 ft.
Overall Length	27 ft.
RUNNING GEAR	
Axles	10,000 lbs. Belshe Axles (x2)
Brakes	Electric
Suspension	7-Leaf 3 in. Slipper Spring
Wheels	17.5 in. 10-Bolt Superior Single
Tires	235 75R 17.5
FRAME MATERIAL	
Outer Rails & Central Beam	3 in. x 6 in. x 0.375 Angle A-36; 3 in. x 5 in. x 0.25 in. tube A-36 (x2)
Cross Members	4 in. x 5.4 lb. Channel A-36
Tongue	10 in. x 15.3 lb. Channel A-36
Fender	10 Gauge Formed
LOADING CONFIGURATION	
Ramps	60 in. x 18 in. Ladder Bar Spring Assisted; Adjustable Width
OTHER FEATURES	
Hitch	3 in. Pintle Ring; 24 in. – 31 in. Adjustable Height
Cargo Control	D-Rings
Flooring	2 in. x 8 in. #1 Grade Treated Pine
Jack	12,000 lbs. Drop Leg
Lighting	LED, Sealed Wiring Harness
Paint	Primed, Acrylic Enamel – Black or Yellow Standard

## **OPTIONAL UPGRADES**

✓ Length ✓ Gooseneck

✓ Width
 ✓ Cargo Control

✓ Ramps
✓ Tray Style

✓ Custom Color

✓ Polyurea Coating

✓ Special Machine Packages

Belshe Industries, Inc 12/19/2022