



Belshe Industries, Inc
 PO Box 626
 Tecumseh, OK 74873
 Phone (405) 273-1690
 www.belshetrailers.com

BF11T	HEAVY DUTY LOW PROFILE
--------------	-------------------------------

FEATURE TYPE	STANDARD MODEL FEATURES & MEASUREMENTS
GVWR	23,000 lbs.
TRAILER WEIGHT (MIN)	5,000 lbs.
TRAILER DIMENSIONS	
Deck Length	16 ft.
Width Between Fenders	81.75 in.
Overall Width	102 in.
Dovetail Length	40 in.
Dovetail Width	Full Width
Deck Height	25 in.
Fender Height	10 in.
Tongue Length	80 in.
Ramp Length	5 ft.
Overall Length	27 ft.
RUNNING GEAR	
Axles	11,000 lbs. Belshe Axles (x2)
Brakes	Electric
Suspension	7-Leaf 3 in. Slipper Spring
Wheels	17.5 in. 10-Bolt Superior Single
Tires	235 75R 17.5
FRAME MATERIAL	
Outer Rails & Central Beam	3 in. x 6 in. x 0.375 Angle A-36; 3 in. x 5 in. x 0.25 in. tube A-36 (x2)
Cross Members	4 in. x 5.4 lb. Channel A-36
Tongue	10 in. x 15.3 lb. Channel A-36
Fender	10 Gauge Formed
LOADING CONFIGURATION	
Ramps	60 in. x 18 in. Ladder Bar Spring Assisted; Adjustable Width
OTHER FEATURES	
Hitch	3 in. Pintle Ring; 24 in. – 31 in. Adjustable Height
Cargo Control	D-Rings
Flooring	2 in. x 8 in. #1 Grade Treated Pine
Jack	12,000 lbs. Drop Leg
Lighting	LED, Sealed Wiring Harness
Paint	Primed, Acrylic Enamel – Black or Yellow Standard

OPTIONAL UPGRADES

- | | | | |
|----------|-----------------|--------------------|----------------------------|
| ✓ Length | ✓ Gooseneck | ✓ Custom Color | ✓ Special Machine Packages |
| ✓ Width | ✓ Cargo Control | ✓ Polyurea Coating | |
| ✓ Ramps | ✓ Tray Style | | |